

ARCHITECTURAL

GRATES + DRAINS



65Tii25MTL **Tile Insert Drain**

All stainless steel drainage unit made to specified length with specified outlet position.

The 65Tii25 is a Tile Insert Drain manufactured from 1.5mm thick 316 marine grade stainless steel.

Suitable for tiles up to 10mm thick.


The maximum length of the tile insert will be 1200mm in one piece, channels longer than 1200mm will have inserts in multiple equal sections

SPECIFICATIONS + DIMENSIONS

Channel Width Channel Depth Length(s) **Outlet Size**

72mm 27mm As Required DN40, DN50, DN65

STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

PRODUCT APPLICATIONS

Bathroom Drainage Aged / Health Care Drainage **Balcony Drainage Commercial Drainage** Courtyard / Patio Drainage Hospitality Drainage

Shower Drainage Multi-Residential Drainage Special Needs Drainage Threshold Drainage Suspended Slab Drainage Wet Area Drainage


Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown Downloaded 15/09/2025 (please check for updates)



Visit **stormtech.com.au** for tools + inspiration.



Code 65Tii25MTL Range 65 Grate Style Ti Category Made-to-Length Channel Material Stainless Steel Steel Grade 316



Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions